

802 WD Z2-22 M / T

Zone 2 - 22 ATEX certified industrial vacuum

The 802 WD Z2 - 22 is an ATEX certified industrial vacuum ideal for suction of liquids, even in hazardous environments that require Zone 2 or 22 ATEX certification. The double filtration kit (wet or dry) supplied and the floating device, useful to stop the vacuum when container is full, allow the maximum durability of this powerful industrial vacuum, maintaining its best performances

Main Features:

- Double ATEX certificate (machine and motor)
- Maintenance free motor, very silent and suitable for 24/7 continuous duty
- Stainless steel container standard
- Double stage dry filter with integrated self cleaning system
- Integrated floating device and PPL filter for liquids
- Integrated pressure relief valve



MODELS AND DATASHEET

MODELS	802 WD Z2-22 M / T
Power (Voltage)	230 1 ~ / 400 3~
Frequency (Hz)	50
Power (kw)	2.2
Depression (mmH2O)	1800
Airflow max. (m3/h)	250
Surface (cm2)	8000
Filtration class — primary filter (IEC 60335-2-69)	M
Filter surface — HEPA filter (cm2)	20,500
Filtration class — HEPA filter (EN1822)	H14
Capacity (Litres)	80
Floating	SI
Suction inlet diameter (mm)	80
Sound level — dB(A)	70
IP protection / Ins.Cl. (IP)	67
Dimensions (cm)	53 x 66 x 120H
Weight (kg)	43
ATEX Zone (Directive 94/9/CE)	2/22
Marking type (Directive 94/9/CE)	3GD

